

## WIDE BELT SANDER



MODEL	RP RXF 100	RP RXF 200
Machine Name	1 Head Wide Belt Sander	2 Head Wide Belt Sander
Max. Working Width	40-1300 mm	40-1300 mm
Working Thickness	2.5-80 mm	2.5-80 mm
Working Length	>580 mm	>580 mm
Speed of Feeding	6-45 M/Min	6-45 M/Min
Revolving Speed of 1st Sanding Belt	18 M/S	18 M/S
Revolving Speed of 2nd Sanding Belt	-	14 M/S
Size of Sanding 1st Belt (WxC)	1330 x 2200 mm	1330 x 2200 mm
Size of Sanding 2nd Belt (WxC)	-	1330 x 2200 mm
Roller Diameter	210 mm	210 mm
Motor Power of 1st Sanding Unit	22 kw	22 kw
Motor Power of 2nd Sanding Unit	-	15 kw
Motor Power of Feeding	4 kw	4 kw
Motor Power of Thickness Adjustment	0.55 kw	0.55 kw
Motor Power of Brush Roller	-	0.37 kw
Motor Power of Vacuum Table	-	3 kw
Total Motor Power	26.55 kw	44.92 kw
Power Supply Requirement	415 V/AC, 50HZ, 3 Phase	415 V/AC, 50HZ, 3 Phase
Compressed Air Pressure	0.55 MPA	0.55 MPA
Compressed Air Consumption	0.43 M <sup>3</sup> /Min	0.76 M <sup>3</sup> /Min
Dust Extraction Requirement	4200 M <sup>3</sup> /H	8000 M <sup>3</sup> /H
Min. Sucked Air Velocity	25-30 M/S	25-30 M/S
Dia. of Dust Hood Outlet for Sanding Unit	200 mm x 1 PCS	200 mm x 2 PCS
Dis. of Dust Hood Outlet for Brush Roller	-	1500 mm x 2 PCS
Machine Overall Size (L x W x H)	1580 x 1960 x 2160 mm	1950 x 2530 x 1970 mm
Machine Weight	~ 2200 KG	~ 2750 KG

- Heavy Duty Construction
- User Friendly
- Electrical Control Panel Fully Automatic
- Cost Effective
- Stable Performance & High Production Efficiency
- Hi-tech Machinery & Speed Technology
- Vibration Free Construction
- Blower to Remove Dust
- Brusher (Optional)